

Janus Terminus Gateway Products Comparison

Module	Voltage Range	Operating Temp	Network	GPS	GPIO	ADC	DAC	Dimension	Enclosure	Connectivity	Certifications
HSPA910T2 v1.00	7-32 Vdc	-40° to 65° C	HSPA+ GSM/GPRS EDGE, UMTS	Yes	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace;; USB OTG; CAN; RS-485	PTCRB; CE AT&T T-Mobile, Rogers
LTE910T2 CAT1 v6.00 - Verizon	7-32 Vdc	--40° to 65° C	LTE	Yes	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace; USB OTG; CAN; RS-485	Verizon
LTE910T2 CAT1 v7.00 - AT&T	7-32 Vdc	-40° to 65° C	LTE	Yes	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace; USB OTG; CAN; RS-485	PTCRB; CE AT&T
LTE910T2 CAT-M1 — Products Coming Soon											
HSPA910T3 v1.00	5 Vdc	-40° to 85° C	HSPA+ GSM/GPRS EDGE, UMTS	Yes	0	0	0	5.2142 x 2.350 x 1.81"	Aluminum Enclosure	DB9 RS-232; USB	PTCRB; CE AT&T T-Mobile, Rogers
LTE910T3 CAT3 v1.00 - AT&T	5 Vdc	-40° to 85° C	LTE HSPA+ GSM/GPRS EDGE, UMTS	Yes	0	0	0	5.2142 x 2.350 x 1.81"	Aluminum Enclosure	DB9 RS-232; USB;	PTCRB AT&T
LTE910T3 CAT-M1 — Products Coming Soon											
LTE910T3 CAT1 v6.00 - Verizon	5 Vdc	-40° to 85° C	LTE	Yes	0	0	0	5.2142 x 2.350 x 1.81"	Aluminum Enclosure	DB9 RS-232; USB;	Verizon
LTE910T3 CAT1 v7.00 - AT&T	5 Vdc	-40° to 85° C	LTE	Yes	0	0	0	5.2142 x 2.350 x 1.81"	Aluminum Enclosure	DB9 RS-232;	PTCRB AT&T
LTE910T3X CAT4 — Products Coming Soon											
LTE910T3M — Products Coming Soon											

Janus Terminus Gateway Products Comparison

Module	Voltage Range	Operating Temp	Network	GPS	GPIO	ADC	DAC	Dimension	Enclosure	Connectivity	Certifications
HSPA400AP v1.00	7-26 Vdc	40° to 85°C	HSPA+ GSM/GPRS EDGE, UMTS	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS485; CAN; USB Host; Ethernet	PTCRB; CE AT&T T-Mobile, Rogers
LTE400AP CAT1 v6.00 Verizon	7-26 Vdc	40° to 85°C	LTE	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS485; CAN; USB Host; Ethernet	Verizon
LTE400AP CAT1 v7.00 AT&T	7-26 Vdc	40° to 85°C	LTE	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS485; CAN; USB Host; Ethernet	PTCRB AT&T
LTE400AP CAT-M1 — Products Coming Soon											
LTE910PS CAT1 v1.00 - AT&T,	7-15 Vdc	-40° to 60°C	LTE HSPS+, GSM/GPRS EDGE, UMTS	Yes	0	0	0	6.5 x 4.3 x 1.2"	Aluminum Enclosure	DB9 RS-232 for configuration and Data; RJ11 for Telephone Equipment	
LTE910PS CAT1 v3.00 - Verizon	7-15 Vdc	-40° to 60°C	LTE	Yes	0	0	0	6.5 x 4.3 x 1.2"	Aluminum Enclosure	DB9 RS-232 for configuration and Data; RJ11 for Telephone Equipment	