

# Janus Terminus Gateway Products Comparison

Module	Voltage Range	Operating Temp	Network	GPS	GPIO	ADC	DAC	Dimension	Enclosure	Connectivity	Certifications
CDMA910T2 v2.00 - Sprint v3.00 - Verizon	7-32 Vdc	-40° to 65°C	CDMA 1XRTT	No	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace; USB OTG; CAN; RS-485	Sprint Verizon CE
EVDO910T2 v2.00 - Sprint v3.00 - Verizon	7-32 Vdc	-40° to 65°C	EV-DO CDMA	Yes	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace; USB OTG; CAN; RS-485	Sprint Verizon CE
HSPA910T2 v1.00	7-32 Vdc	-40° to 65°C	HSPA+ GSM/GPRS EDGE, UMTS	Yes	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace;; USB OTG; CAN; RS-485	PTCRB; CE AT&T T-Mobile, Rogers
LTE910T2 v1.00 - AT&T	7-32 Vdc	-40° to 65°C	LTE HSPA+, GSM/GPRS EDGE, UMTS	Yes	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace; USB OTG; CAN; RS-485	PTCRB AT&T - Sept '16
LTE910T2 v3.00 - Verizon	7-32 Vdc	-40° to 65°C	LTE	Yes	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace; USB OTG; CAN; RS-485	Verizon
LTE910T2 v6.00 - Verizon	7-32 Vdc	--40° to 65°C	LTE	Yes	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace; USB OTG; CAN; RS-485	Verizon
LTE910T2 v7.00 - AT&T	7-32 Vdc	-40° to 65°C	LTE	Yes	14	8	2	2.6 x 3.75 x 1.2"	Ryton Enclosure	DB9 RS-232; 50 Pin Header; CMOS Level UART for AT/Trace; USB OTG; CAN; RS-485	PTCRB; CE AT&T
CDMA910T3 v2.00 - Sprint v3.00 - Verizon	5 Vdc	-40° to 85°C	CDMA 1XRTT	No	0	0	0	5.2142 x 2.350 x 1.81"	Aluminum Enclosure	DB9 RS-232; Sprint USB	Verizon
EVDO910T3 v3.00 - Verizon	5 Vdc	-40° to 85°C	EV-DO CDMA	Yes	0	0	0	5.2142 x 2.350 x 1.81"	Aluminum Enclosure	DB9 RS-232; USB	Verizon CE
HSPA910T3 v1.00	5 Vdc	-40° to 85°C	HSPA+ GSM/GPRS EDGE, UMTS	Yes	0	0	0	5.2142 x 2.350 x 1.81"	Aluminum Enclosure	DB9 RS-232; USB	PTCRB; CE AT&T T-Mobile, Rogers
LTE910T3 v1.00 - AT&T	5 Vdc	-40° to 85°C	LTE HSPA+ GSM/GPRS EDGE, UMTS	Yes	0	0	0	5.2142 x 2.350 x 1.81"	Aluminum Enclosure	DB9 RS-232; USB;	PTCRB AT&T - Sept '16
LTE910T3 v3.00 - Verizon	5 Vdc	-40° to 85°C	LTE	Yes	0	0	0	5.2142 x 2.350 x 1.81"	Aluminum Enclosure	DB9 RS-232; USB;	Verizon

# Janus Terminus Gateway Products Comparison

Module	Voltage Range	Operating Temp	Network	GPS	GPIO	ADC	DAC	Dimension	Enclosure	Connectivity	Certifications
CDMA400AP v5.00 - Sprint v6.00 - Verizon	7-26 Vdc	-40° to 85°C	CDMA 1XRTT	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS485; CAN; USB Host; Ethernet	Sprint CE Verizon
HSPA400AP v1.00	7-26 Vdc	40° to 85°C	HSPA+ GSM/GPRS EDGE, UMTS	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS485; CAN; USB Host; Ethernet	PTCRB; CE AT&T T-Mobile, Rogers
EVDO400AP v2.00 - Sprint v3.0 - Verizon	7-32 Vdc	-40° to 85°C	EV-DO CDMA	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS-485; CAN; USB Device; USB Host; Ethernet	Sprint Verizon CE
LTE400AP v1.00 - AT&T	7-26 Vdc	40° to 85°C	LTE HSPS+, GSM/GPRS EDGE, UMTS	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS485; CAN; USB Host; Ethernet	PTCRB AT&T - Sept '16
LTE400AP v3.00 Verizon	7-26 Vdc	40° to 85°C	LTE	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS485; CAN; USB Host; Ethernet	Verizon
LTE400AP v6.00 Verizon	7-26 Vdc	40° to 85°C	LTE	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS485; CAN; USB Host; Ethernet	Verizon
LTE400AP v7.00 AT&T	7-26 Vdc	40° to 85°C	LTE	Yes	4	2	0	3.15 x 4.27 x 1.18"	Aluminum Enclosure	DB9 RS-232 for LINUX DEBUG; RS-232 Level UART; RS485; CAN; USB Host; Ethernet	PTCRB AT&T
HSPA910PS v1.00 - AT&T	7-15 Vdc	-40° to 60°C	HSPA+ GSM/GPRS EDGE, UMTS	Yes	0	0	0	6.5 x 4.3 x 1.2"	Aluminum Enclosure	DB9 RS-232 for configuration and Data; RJ11 for Telephone Equipment	PTCRB AT&T
EVDO910PS v3.00 - Verizon	7-15 Vdc	-40° to 60°C	EV-DO 1XRTT	Yes	0	0	0	6.5 x 4.3 x 1.2"	Aluminum Enclosure	DB9 RS-232 for configuration and Data; RJ11 for Telephone Equipment	Verizon